



New Product Bulletin

Analysis

divtop



• [1]



• [2]

NEW Water-Chek™ H₂O Test Strip

1. Collect a clear water sample in a clean cup (about 1 cup). Water sample must be between 40°F (4°C) and 100°F (38°C).
2. Remove the strip from the foil sealed packet. Do not touch the pads at the end of the strip.
3. Dip the strip in a water sample for 7 seconds with a quick flick and both sections, immerse and shake strip to help in immersing (over-flip).
4. 27 seconds after dipping strip, compare and record results to the following color chart:
 a. Compare pH (0-14) to the color pad on the left.
 b. Compare pH to the color pad on the right.
 c. Compare pH to the color pad on the right.
5. If these readings are not completed, see the instructions on the back of the strip.

HARDNESS	
0-100	100-200
pH	
7.0-8.0	8.0-9.0
CHLORIDE	
0-100	100-200

IF ANY OF THE READINGS FOR HARDNESS, pH, OR CHLORIDE ARE PURCHASE A FULLY FORMULATED HEAVY DUTY PRECHARGED COOLANT MIXTURE TMC-8P 120 (ASTM D200 EG) OR TMC-8P 140 (ASTM D211 PG) or purchase distilled water or deionized water to make pre-charged 50/50 coolant.

Try Fleetguard's High Quality pre-charged coolant products made with Distilled Water:

TMC-8P 120 Pre-Charged Coolant TMC-8P 140 Pre-Charged Coolant TMC-8P 160 Pre-Charged Coolant

For more information on the above pre-charged coolant products, call your Fleetguard Customer Service Representative at 1-800-238-7378.

© 2011 Fleetguard, Inc. or its affiliates. All rights reserved.

• [3]





Every good cooling system maintenance program should include regular coolant testing to determine if the proper level of protection is present or if contaminants exist. A good coolant testing program eliminates guesswork and allows the cooling system to maintain peak performance.

[4] [Learn from our Fleetguard experts in our Coolant Webinar](#)

Search Form

Search

Search

[WHERE TO BUY](#) [5]

Description

