## **SAFETY DATA SHEET**



1. Identification

Product identifier FLEETCOOL EX EG PREMIX (Ethylene glycol based coolant)

Other means of identification

SDS number LT16581a

**Product code** CC2746, CC2745, CC2744, CC2743

**Recommended use** Premixed antifreeze / coolant.

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Cummins Filtration
Address 1200 Fleetquard Road

Cookeville, TN 38506

**United States** 

**Telephone** 24 Hours per day

1-800-22FILTER (1-800-223-4583)

Chemtrec 1-800-424-9300

**E-mail** Not available.

**Emergency phone number** Within Continental U.S.

Outside U.S. Chemtrec 703-527-3887

Supplier Not available.

2. Hazard(s) identification

Physical hazards This mixture does not meet the classification criteria according to OSHA HazCom 2012.

Health hazards Acute toxicity, oral Category 4

Reproductive toxicity Category 2
Specific target organ toxicity, single exposure Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards

This mixture does not meet the classification criteria according to OSHA HazCom 2012.

This mixture does not meet the classification criteria according to OSHA HazCom 2012.

This mixture does not meet the classification criteria according to OSHA HazCom 2012.

Label elements



Signal word Warning

Hazard statement Harmful if swallowed. May cause drowsiness or dizziness. Suspected of damaging fertility or the

unborn child. May cause damage to organs.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. If inhaled: Remove person to fresh air

and keep comfortable for breathing. If exposed or concerned: Call a poison center/doctor. Rinse

mouth.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Material name: FLEETCOOL EX EG PREMIX (Ethylene glycol based coolant)

CC2746, CC2745, CC2744, CC2743 Version #: 03 Revision date: 03-20-2015 Issue date: 03-27-2014

Hazard(s) not otherwise classified (HNOC)

Human poison by ingestion (lethal dose of Ethylene glycol for humans reported to be 100 mL). Symptoms of poisoning may include cyanosis (bluish discolouration of the skin), nausea, dizziness, rapid heartbeat, irregular breathing, coma and death. Initially, the central nervous system is stimulated, followed by depression. Prolonged or repeated ingestion may cause bladder or kidney stones.

Supplemental information

Not applicable.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ETHYLENE GLYCOL	Glycol alcohol 1,2-ETHANDIOL	107-21-1	90 - 100
Diethylene Glycol	2-(2-HYDROXYETHOXY)ETHANOL BIS(2-HYDROXYETHYL) ETHER	111-46-6	0.1 - 0.5
Sodium Nitrite	Nitrous acid, sodium salt	7632-00-0	0.1 - 0.5
Sodium Benzothiazol-2-yl Sulphide	2(3H)-Benzothiazolethione, sodium salt SODIUM 2-MERCAPTOBENZOTHIOLATE	2492-26-4	0.1 - 0.3
Sodium Molybdate	Molybdic acid, Disodium salt	7631-95-0	<= 0.2

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Ingestion

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Not applicable.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

**Hazardous combustion** products

Carbon oxides. Formaldehyde. Other irritating fumes and smoke.

#### Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Value

0.5 mg/m3

Respirable fraction.

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

Sodium Molybdate (CAS

Components

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	••			
Sodium Molybdate (CAS 7631-95-0)	PEL	5 mg/m3		
US. ACGIH Threshold Limit Values Components	Туре	Value	Form	
ETHYLENE GLYCOL (CAS 107-21-1)	Ceiling	100 mg/m3	Aerosol.	

7631-95-0)
US. Workplace Environmental Exposure Level (WEEL) Guides

ComponentsTypeValueDiethylene Glycol (CASTWA10 mg/m3111-46-6)

**TWA** 

**Type** 

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear protective gloves.

Other Wear appropriate chemical-resistant clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. Form Liquid.

CC2746, CC2745, CC2744, CC2743 Version #: 03 Revision date: 03-20-2015 Issue date: 03-27-2014

Color Pink.

Characteristic odour. Odor

**Odor threshold** Not available. 10.0 - 10.5 pН Not available. Melting point/freezing point Initial boiling point and boiling 224.6 °F (107 °C)

range

Not available. Flash point Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Not available. Vapor pressure

2.1 Vapor density

Relative density Not available.

Solubility(ies)

Solubility (water) Completely miscible

Partition coefficient (n-octanol/water)

Not available.

**Auto-ignition temperature Decomposition temperature** 

Not available. Not available. Not available.

Other information

1.04 - 1.07 Specific gravity

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

**Viscosity** 

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Acids. Strong oxidizing agents. Alkali metals. Halogenated materials. Alkalies. Ketones. Incompatible materials

Hazardous decomposition

products

Carbon oxides. Formaldehyde. Other irritating fumes and smoke.

#### 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Prolonged inhalation may be harmful. May cause damage to organs by inhalation.

No adverse effects due to skin contact are expected. Skin contact Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Kidney injury may occur. Harmful if swallowed. May cause damage to organs by ingestion. Most important

symptoms/effects, acute and

delayed

Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

#### Information on toxicological effects

**Acute toxicity** Harmful if swallowed. Narcotic effects.

Components **Species Test Results** Diethylene Glycol (CAS 111-46-6) **Acute** Dermal LD50 Rabbit 13300 mg/kg Inhalation LC50 Rat > 5.08 mg/lOral LD50 Rat 25300 mg/kg ETHYLENE GLYCOL (CAS 107-21-1) **Acute** Dermal LD50 Rabbit 9530 mg/kg Inhalation LC50 Rat 10.92 mg/l, 4 hours Oral LD50 Human 1110 - 1665 mg/kg Rat 4000 mg/kg Sodium Benzothiazol-2-yl Sulphide (CAS 2492-26-4) **Acute** Dermal LD50 Rabbit > 1250 mg/kg Inhalation LC50 Rat > 8200 mg/m<sup>3</sup>, 6 hours Oral LD50 Rat 5200 mg/kg Sodium Molybdate (CAS 7631-95-0) Acute Dermal LD50 Rabbit No data in literature Inhalation LC50 Rat > 2.08 mg/l, 4 Hours Oral LD50 Rat 4040 mg/kg Sodium Nitrite (CAS 7632-00-0) Acute Dermal LD50 Rabbit No data in literature Inhalation LC50 Rat No data in literature Oral

Rat

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

LD50

Respiratory sensitization Not available.

**Skin sensitizer** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

85 mg/kg

mutagenic or genotoxic.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

May cause damage to organs. Kidney injury may occur. Narcotic effects. Causes damage to

organs by ingestion.

Specific target organ toxicity -

repeated exposure

Not classified.

Not available. Aspiration toxicity

Prolonged inhalation may be harmful. **Chronic effects** 

#### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Diethylene Glycol (CA	S 111-46-6)		
Aquatic			
Acute			
Algae	EC10	Green plankton algae (Chlorococcales)	1000 mg/l, 24 Hours
Crustacea	EC50	Water flea (Daphnia magna)	48900 mg/l, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	77900 mg/l, 96 hours
ETHYLENE GLYCOL	(CAS 107-21-1)		
Acute			
	LC50	Rainbow trout (Oncorhynchus mykiss)	22810 mg/l, 96 Hours
Aquatic			
Crustacea	LC50	Water flea (Daphnia magna)	46300 - 57000 mg/l, 48 hours
Acute			
Algae	IC50	Green algae (Selenastrum capricornutum)	10940 mg/l, 96 Hours
	NOEC	Green algae (Selenastrum capricornutum)	10000 mg/l, 96 Hours
Sodium Benzothiazol-	2-yl Sulphide (CAS	2492-26-4)	
Aquatic			
Acute			
Algae	EC50	Green algae (Selenastrum capricornutum)	0.4 mg/l, 72 Hours
Crustacea	EC50	Water flea (Daphnia magna)	19 mg/l, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	0.8 mg/l, 96 Hours
Sodium Molybdate (C	AS 7631-95-0)		
Aquatic			
Acute			
Crustacea	LC50	Water flea (Daphnia magna)	3220 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2911 mg/l, 96 hours
Chronic			
Crustacea	NOEC	Water flea (Daphnia magna)	50 mg/l, 21 days
Fish	NOEC	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	200 mg/l, 32 days
Sodium Nitrite (CAS 7	632-00-0)		
Acute			
	LC50	Rainbow trout (Oncorhynchus mykiss)	0.54 mg/l, 96 hours

Material name: FLEETCOOL EX EG PREMIX (Ethylene glycol based coolant)

SDS US 6/9 CC2746, CC2745, CC2744, CC2743 Version #: 03 Revision date: 03-20-2015 Issue date: 03-27-2014

Components		Species	Test Results	Test Results	
Aquatic					
Acute					
Algae	EC50	Green Algae (Scenedesmus subspicatus)	> 100 mg/l, 72 hours		
Crustacea	EC50	Water flea (Daphnia magna)	15.4 mg/l, 48 hours		
Chronic					
Algae	NOEC	Green Algae (Scenedesmus subspicatus)	100 mg/l, 72 hours		

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Diethylene Glycol -1.5 ETHYLENE GLYCOL -1.36

**Bioconcentration factor (BCF)** 

Diethylene Glycol 3
ETHYLENE GLYCOL 10

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

#### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and

the IBC Code

#### 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Sodium Nitrite (CAS 7632-00-0) 1.0 % One-Time Export Notification only.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

ETHYLENE GLYCOL (CAS 107-21-1) Listed. Sodium Nitrite (CAS 7632-00-0) Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

#### SARA 313 (TRI reporting)

	Chemical name	CAS number	% by wt.
	ETHYLENE GLYCOL	107-21-1	90 - 100
;	Sodium Nitrite	7632-00-0	0.1 - 0.5

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYLENE GLYCOL (CAS 107-21-1)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### US state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

#### **US. Massachusetts RTK - Substance List**

ETHYLENE GLYCOL (CAS 107-21-1)

Sodium Nitrite (CAS 7632-00-0)

#### US. New Jersey Worker and Community Right-to-Know Act

ETHYLENE GLYCOL (CAS 107-21-1)

Sodium Nitrite (CAS 7632-00-0)

### US. Pennsylvania Worker and Community Right-to-Know Law

Diethylene Glycol (CAS 111-46-6)

ETHYLENE GLYCOL (CAS 107-21-1)

Sodium Nitrite (CAS 7632-00-0)

#### **US. Rhode Island RTK**

ETHYLENE GLYCOL (CAS 107-21-1)

Sodium Nitrite (CAS 7632-00-0)

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes

Country(s) or region Inventory name On inventory (yes/no)\*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

 Issue date
 03-27-2014

 Revision date
 03-20-2015

Version # 03

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Prepared by: ICC The Compliance Center Inc. 1-888-442-9628

http://www.thecompliancecenter.com

Disclaimer

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by / obtained from Cummins Filtration and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc. and Cummins Filtration expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or

in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Cummins Filtration

**Revision Information** GHS: Classification **Bibliography** Not available.

Material name: FLEETCOOL EX EG PREMIX (Ethylene glycol based coolant)

CC2746, CC2745, CC2744, CC2743 Version #: 03 Revision date: 03-20-2015 Issue date: 03-27-2014