

Fleetcool EG Premix (50-50 and 40-60)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 06/06/2016

Revision date: 06/24/2020

Version: 3.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product code : Fleetcool EG Premix 50-50
Product code: CC2886, CC8970, CC8971, CC8972, CC8973, CC8974, CC8974 X

Fleetcool EG Premix 40-60
Product code: CC8985, CC8995MX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Premix Antiboil/Antifreeze Coolant

1.3. Details of the supplier of the safety data sheet

Manufacturer

Cummins Filtration
1200 Fleetguard Road
Cookeville, TN 38506 - USA
T 1-800-22-FILTER (1-800-223-4583)

Distributor

Cummins Western Canada
Canadian Distributor
11751 181 St.
Edmonton, AB T5S 2K5 - Canada
T 1-780-455-2151

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300 (Within Continental U.S.)
Chemtrec 703-527-3887 (Outside the U.S.).

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Acute Tox. 4 (Oral)
STOT SE 1
STOT SE 3

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS07

GHS08

Signal word (GHS) :

Danger

Hazard statements (GHS) :

Harmful if swallowed. May cause respiratory irritation. Causes damage to organs.

Precautionary statements (GHS) :

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. If swallowed: Call a poison center or doctor if you feel unwell. Rinse mouth. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed: Call a poison center/doctor. Call a poison center or doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Fleetcool EG Premix (50-50 and 40-60)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

3.2. Mixtures

Name	Product identifier	%
Ethylene glycol	(CAS-No.) 107-21-1	30 – 60

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand. Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to cool exposed surfaces.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

Fleetcool EG Premix (50-50 and 40-60)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not breathe dust, fume, gas, mist, spray, vapours. Avoid contact with skin and eyes. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Ethylene oxide is subject to the standard 29 CFR 1910.1047 which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements.
- Hygiene measures : Wash hands before eating, drinking, or smoking. Launder contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Keep only in original container. Keep in a cool, well-ventilated place. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylene glycol (107-21-1)		
ACGIH	ACGIH TWA (ppm)	25 ppm (vapor fraction)
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (inhalable particulate matter, aerosol only)
ACGIH	ACGIH STEL (ppm)	50 ppm (vapor fraction)

8.2. Exposure controls

- Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. Ensure good ventilation of the work station.
- Hand protection : Wear suitable gloves.
- Eye protection : Safety glasses or goggles are recommended when using product.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Environmental exposure controls : Avoid release to the environment.
- Other information : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Green Liquid
- Colour : Green
- Odour : Odourless
- Odour threshold : No data available
- pH : 10.5
- Melting point : No data available
- Freezing point : No data available
- Boiling point : 220 – 226 °F / 104.4 – 107.8 °C
- Flash point : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Flammability (solid, gas) : Not flammable
- Vapour pressure : No data available
- Relative vapour density at 20 °C : No data available
- Relative density : 1.06 – 1.071
- Solubility : No data available
- Partition coefficient n-octanol/water : No data available

Fleetcool EG Premix (50-50 and 40-60)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Incompatible materials.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Fleetcool EG Premix (50-50 and 40-60)	
ATE CA (oral)	959.802 mg/kg bodyweight

Ethylene glycol (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rat	10600 mg/kg

Skin corrosion/irritation	: Not classified. pH: 10.5
Serious eye damage/irritation	: Not classified. pH: 10.5
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: Causes damage to organs. May cause respiratory irritation.

Ethylene glycol (107-21-1)	
STOT-single exposure	Causes damage to organs. May cause respiratory irritation.

STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Fleetcool EG Premix (50-50 and 40-60)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Ethylene glycol (107-21-1)	
LC50 fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	14 – 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
NOEC chronic crustacea	4.2 mg/l

12.2. Persistence and degradability

Fleetcool EG Premix (50-50 and 40-60)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Fleetcool EG Premix (50-50 and 40-60)	
Bioaccumulative potential	Not established.

Ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water	-1.93

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment. No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

Not regulated

SECTION 15: Regulatory information

15.1. Federal regulations


All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Revision date : 06/24/2020

06/24/2020

US-CAN (English)

CC2886, CC8970, CC8971, CC8972, CC8973, CC8974, CC8974 X and CC8985, CC8995MX

5/6

Fleetcool EG Premix (50-50 and 40-60)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Other information : None.
Prepared by : Nexreg Compliance Inc.
Prepared for : Cummins Filtration

Indication of changes:

SDS update, GHS Classification

SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.